



A.T.F. TYPE DEXRON III

Universal Automatic Transmission Fluid

Description

ATF Type Dexron III is a premium automatic transmission fluid, specially developed for the electronic controlled transmissions, which run at high operating temperatures. This fluid has the following properties:

- An excellent viscosity, even at low temperatures
- A very low pour point
- Smooth shifting without vibrations
- A positive activity against wear, corrosion and foam
- An excellent stability against oxidation
- Perfect compatibility with seals and non-ferro metals

Quality level

GM: DEXRON III F/G
MB: 236.9
FORD: MERCON
ALLISON: C4
VOITH

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

ATF Type Dexron III can be used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the constructors prescribe an oil, which meets the General Motors ATF Type Dexron III or Dexron IID, IIE and Ford Mercon requirements.

Photo



Typical properties

Density 15°C	0.864
Viscosity cst 40°C	32.2
Viscosity cst 100°C	8.2
Viscosity index	210
Pourpoint °C	-45
Flashpoint COC °C	196

Average oil analysis without engagement

DENICOL
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com