



---

# CENTRAL H.V.I. HYDRAULIC FLUID

Multifunctional Full Synthetic Hydraulic Fluid

---

## Description

Central HVI Hydraulic Fluid is a full synthetic oil, based on conscientiously selected high quality base oils. This multifunctional hydraulic oil is:

- Suitable for use in most various systems
- Within a large range of temperature
- Very high viscosity index
- Excellent oxidation stability
- Prevents formation of rust and foam
- Reduces wear by a friction-reducing additive
- Reduces production of sound by a hydraulic pump

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

Central HVI Hydraulic Fluid is utmost suitably for:

- Hydro pneumatic suspension systems en hydrostatic drives
- Hydraulic clutches and power steering systems
- Level control and electro-hydraulic folding roof controllers

## Photo



## Typical properties

Density 15°C	0.824
Viscosity cst 40°C	13.4
Viscosity cst 100°C	5.2
Viscosity index	400
Pourpoint °C	-48
Flashpoint COC °C	131

Average oil analysis without engagement

**DENICOL**  
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)