



# PREMIUM OIL SAE 10W-20W-30-40-50

Mineral Mono-grade Engine Oil

## Description

Premium Oil is a pure, mineral engine oil, based on extremely high quality solvent-refined base oils, to which an antifoam additive was added, which prevents oxidation and corrosion. This oil has a low content of carbon residue and a high natural viscosity index. It offers a total protection and cleaning of the engine.

## Quality level

API SA

## Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.  
Barrels of 30, 60 and 208 L.

## Application

This oil is suitable for systems, in which the oil is not charged too heavily, such as bearings in pumping stations, lightly charged gearboxes or lubricating circulation systems.

## Photo



## Typical properties

	SAE 10W	SAE 20W	SAE 30	SAE 40	SAE 50
	ISO 32	ISO 46/68	ISO 100	ISO 150	ISO 220
Density 15°C	0.870	0.880	0.883	0.890	0.895
Viscosity cst 40°C	58	58	100	152	210
Viscosity cst 100°C	5.5	8.3	11.2	14.6	18
Viscosity index	114	113	97	94	93
Pourpoint °C	-31	-23	-23	-16	-9
Flashpoint COC °C	221	234	251	256	259

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)