



SHOCK FLUID H.V.I. 400

Extreme Competition

Description

Shock Fluid H.V.I. 400 is an excellent shock oil with:

- Outstanding anti-wear characteristics. It extends equipment life and reduces maintenance and downtime.
- Strong oxidation and thermal stability.
- Reusable after water is removed because Shock Fluid H.V.I. 400 separates water readily without loss of performance additives.
- Extended oil change intervals.
- Very high viscosity index.
- Dyno and track tested
- For all aluminium and steel bodies
- SAE viscosity grade between SAE 3.5 to SAE 7.5 due to the very high viscosity index

Available in

Carton of 24x1 L.
Barrels of 30, 60 and 208 L.

Application

For all aluminium and steel bodies.

Photo



Typical properties

Viscosity cst 40°C	13.4
Viscosity cst 100°C	5.16
Viscosity index	395
Pourpoint °C	-48
Flashpoint COC °C	145
Four ball wear test, scar diam. (mm) 1 hour @40 kg, 1200rpm @75°C/167°F	0.75

Average oil analysis without engagement

DENICOL
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com