



SUPRA SYN GEN2 5W30

Full Synthetic Engine Oil

Description

Supra Syn GEN2 5W30 is a full synthetic lubricant, based on a selection of high qualified base oils of excellent quality. Intended for petrol engines with fuel injection, also with turbo charge and more valves per cylinder of American and Asian passenger cars, SUV's and light vans with the following features:

- Very good friction and anti-wear characteristics
- Reduces sludge
- Improves cold start
- Excellent fluidity at low temperatures
- Lower fuel consumption and reduced CO2 emissions

Quality level

API	SN/RC - SN Plus
CHRYSLER	MS 6395
FORD	WSS-M2C945-A - WSS-M2C946-A - WSS-M2C947-A
GM	Dexos1™ Gen 2
ILSAC	GF-5

Available in

Cartons of 24x1 L, 12x2 L, 6x4 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

Containable for petrol engines with fuel injection, also with turbo charge and more valves per cylinder of American and Asian passenger cars, SUV's and light vans.

Photo



Typical properties

nsity 15°C	0.850
Viscosity cst 40°C	60.3
Viscosity cst 100°C	10.3
Viscosity index	165
Pourpoint °C	-47
CCS-viscosity -30°C	5805
Sulphated Ash	0.95
Flashpoint COC °C	210

Average oil analysis
without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com