



0

SYN GEAR OIL EP L.S. SAE 75W140

Synthetic Extreme pressure Limited slip Transmission oil

Description

Syn Gear Oil EP L.S. 75W140 is a synthetic gear oil, composed of paraffinic base oils and selected additives, especially designed for the lubrication of the so called "Limited slip" and "Auto-locked" hypoid transmissions.

- Excellent frictional properties guarantees a smooth shift performance.
- A very good anti-wear protection assures a longer transmission life.
- Extended oil life: proves resistance to oil degradation.
- Excellent anti-wear, anticorrosion and anti-oxidation properties.
- Prolonged life time of the transmission.

Quality level

API: GL-5
MIL: L-2105 B/C/D
BMW: MSP/A

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

For the lubrication of the so called "Limited slip" and "Auto-locked" hypoid transmissions. Especially designed for the lubrication of the so called "Limited slip". Highly recommended for 4x4-vehicles

Photo



Typical properties

Density 15°C	0.905
Viscosity cst 40°C	170
Viscosity cst 100°C	26.5
Viscosity index	195
Pourpoint °C	-52
Flashpoint COC °C	161

Average oil analysis without engagement

DENICOL
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com