



ATF TYPE D

Automatic Transmission Fluid

Description

ATF Type D is an extremely high-graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- A very high and stable viscosity index
- A very low pourpoint
- An excellent stability against oxidation
- A positive activity against wear, corrosion and foam
- Specific friction-properties
- Perfect compatibility with seals and non-ferro metals

Quality level

GM	DEXRON II D
ALLISON	C3/C4
MB	236.7
ZF	TE-ML 03D/04D/11A/14A/17C
CATERPILLAR	TO-2
FORD	M2C138-CJ/166-H/185-A SQ-M9010-B

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

ATF Type D may be used for automatic gear-boxes, power-steering, torque convertors and other equipment, for which an ATF DEXRON 2D fluid is required.

Photo



Typical properties

Density 15°C	0.873
Viscosity cst 40°C	43.5
Viscosity cst 100°C	8.30
Viscosity index	173
Pourpoint °C	-45
Flashpoint COC °C	205

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com