



# SPECIAL DIESEL SAE 10W-20W20-30-40-50

Monograde Diesel Engine Oil - For Severe Conditions

## Description

Special Diesel SG/CE is a universal oil of high quality, intended for all diesel engines (with compressor or with natural aspiration) and gasoline engines in all working conditions.

The monograde oil is particularly recommended for diesel engines of passenger cars, fixed or mobile equipment and trucks.

- Strong detergent and dispersant power
- Reinforced anti-wear power
- High thermic stability and resistance against ageing
- Excellent protection against corrosion and rust

## Quality level

API	SG-CE
MERCEDES MB	227.0/228.0
MIL	MIL-L-46152 B, MIL-L-2104 C/D
ALLISON	C3 (only for SAE 10W)

## Available in

Barrels of 30, 60 and 208 L.

## Application

Special Diesel SG/CE is highly recommended for the most diesel engines with or without turbo and 4-stroke gasoline engines and LPG, for which an AP-class SG is required.

## Photo



## Typical properties

	SAE 10W	SAE 20W20	SAE 30	SAE 40	SAE 50
Density 15°C	0.883	0.888	0.892	0.895	0.900
Viscosity cst 40°C	36.7	57	98	150	210
Viscosity cst 100°C	3.1	7.8	10.9	14.7	18.5
Viscosity index	112	101	95	97	96
Pourpoint °C	-24	-22	-18	-12	-10
Flashpoint COC °C	212	220	235	240	250

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
 URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)