



SYNTRUCK UHPD SAE 10W40

Ultra High Performance Diesel Engine Oil

Description

Syntruck UHPD is a synthetic Ultra High Performance Diesel (UHPD) engine oil, meeting the highest performance standards for large trucks.

Quality level

API	CI-4
MB	228.5
MAN	M 3277
ACEA	E7-08
VOLVO	VDS-3
MTU	Type 3
MACK	EOM Plus

Available in

Barrels of 30, 60 and 208 L.

Application

Intended for truck fleet operators, seeking the best available lubrication technology, in order to meet the increasingly stringent emission limits that are imposed on diesel engines in Europe, and the United States.

Lower fuel consumption and CO₂ emission.

Photo



Typical properties

	SAE 10W40
Density 15°C	0.872
Viscosity cst 40°C	91
Viscosity cst 100°C	12.02
Viscosity index	161
Pourpoint °C	-36
Flashpoint COC °C	230

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> ● EMAIL denicol@denicol.com